

BR2A MARTILLO DE FONDO DTH

BR2A Martillo	Descripción del Artículo	Peso kg	Número de parte
---------------	--------------------------	---------	-----------------



1	Top Sub	2.95	BR2A-TSUB
2	Check Valve	0.10	BR2A-CVALVE
3	Spring	0.05	BR2A-SPRING
4	Air Distributor	0.40	BR2A-DIST
5	Internal Cylinder	0.85	BR2A-ICYL
6	Piston	2.70	BR2A-PISTON
7	External Cylinder	5.35	BR2A-ECYL
8	Guided Sleeve	0.55	BR2A-BUSH
9	"O" Ring Stop Ring	0.005	BR2A-SR-SRING
10	Stop Ring	0.10	BR2A-SRING
11	Drive Chuck	1.05	BR2A-DCHUCK
12	Drill Bit		BR2A-77FF-TV

Datos técnicos

Largo(sin broca)	Peso(sin broca)	Diámetro externo	Vástago de broca	Rango de agujeros	Hilo de conexión
880mm	14.1kg	Φ62mm	BR2	Φ76- Φ90	RD 50 BOX
Tamaño de caja	Tasa de impacto a 1.7Mpa	Velocidad de rotación recomendada	Consumo de aire		
			80-170(PSI)		
910x90x120mm	25Hz	25-40r/min	250-350(CFM)		