

HK4-D MARTILLO DE FONDO DTH

HK4-D Martillo	Descripción del Artículo	Peso kg	Número de parte
----------------	--------------------------	---------	-----------------



1	Top Sub	6.50	HK4D-TSUB
2	"O" Ring of Top Sub	0.01	HK4D-SR-TSUB
3	Check Valve	0.35	HK4D-CVALVE
4	Spring	0.05	HK4D-SPRING
5	Compression Buffer	0.15	HK4D-CBUFFER
6	Air Distributor	2.10	HK4D-DIST
7	Internal Cylinder	2.25	HK4D-ICYL
8	Piston	8.50	HK4D-PISTON
9	External Cylinder	15.2	HK4D-ECYL
10	Retainer Ring	0.02	HD4D-RRING
11	Guided Sleeve	1.30	HK4D-BUSH
12	Bush Retaining Ring	0.02	HK4D-BUSH-RRING
13	"O" Ring of Stop Ring	0.01	HK4D-SK-SRING
14	Stop Ring	0.30	HK4D-SRING
15	Drive Chuck	3.40	HK4D-DCHUCK
16	Drill Bit		HK4D-110FF-TV

Datos técnicos

Largo(sin broca)	Peso(sin broca)	External Diameter	Vástago de broca	Rango de agujeros	Hilo de conexión
922mm	38.0Kg	Φ100mm	DHD340A Cop44	Φ112- Φ127	API 2 3/8" REG CUBEX # 24
Tamaño de caja	Tasa de impacto a 1.7Mpa	Velocidad de rotación recomendada	Consumo de aire		
1010x130x160mm	25Hz	30-70r/min	200-300(PSI)		
			500-700(CFM)		