

HQL40A MARTILLO DE FONDO DTH

HQL40A Martillo	Descripción del Artículo	Peso kg	Número de parte
-----------------	--------------------------	---------	-----------------



1	Top Sub	6.50	HQL40A-TSUB
2	"O" Ring of Top Sub	0.01	HQL40A-SR-TSUB
3	Check Valve	0.35	HQL40A-CVALVE
4	Spring	0.05	HQL40A-SPRING
5	Air Distributor	1.50	HQL40A-DIST
6	Internal Cylinder	2.10	HQL40A-ICYL
7	Piston	8.50	HQL40A-PISTON
8	External Cylinder	15.20	HQL40A-ECYL
9	Guided Sleeve	1.80	HQL40A-GSLEEVE
10	Bush Retaining Ring	0.02	HQL40A-RRING-BUSH
11	"O" Ring of Stop Ring	0.005	HQL40A-SK-SRING
12	Stop Ring	0.20	HQL40A-SRING
13	Drive Chuck	3.20	HQL40A-DCHUCK
14	Drill Bit		HQL40A-115FF-TV

Datos técnicos

Largo(sin broca)	Peso(sin broca)	Diámetro externo	Vástago de broca	Rango de agujeros	Hilo de conexión
1070mm	40.0Kg	Φ99mm	QL40 HQL40	Φ112- Φ127	API 2 3/8" REG CUBEX # 24
Tamaño de caja	Tasa de impacto a 1.7Mpa	Velocidad de rotación recomendada	Consumo de aire		
1230x155x180mm	30Hz	25-40r/min	200-300(PSI)		
			500-700(CFM)		