

HSD10 MARTILLO DE FONDO DTH

HSD10 Martillo	Descripción del Artículo	Peso Kg	Número de parte
	1 Top Sub	63.0	HSD10-TSUB
	2 "O" Ring of Top Sub x1	0.05	HSD10-SK-TSUB
	3 Breakout Ring of Top Sub	1.20	HSD10-TSUB-BRING
	4 Check Valve	1.50	HSD10-CVALVE
	5 Spring	0.20	HSD10-SPRING
	6 Air Distributor	13.0	HSD10-DIST
	7 Internal Cylinder	13.6	HSD10-ICYL
	8 Piston	68.0	HSD10-PISTON
	9 External Cylinder	92.5	HSD10-ECYL
	10 Retaining Ring	0.60	HSD10-RRING
	11 "O" Ring of Stop Ring x1	0.05	HSD10-SK-SRING
	12 Stop Ring	2.80	HSD10-SRING
	13 Guided Sleeve	5.00	HSD10-GSLEEVE
	14 Breakout Ring of Drive chuck	1.20	HSD10-DCHUCK-BRING
	15 Drive Chuck	23.5	HSD10-DCHUCK
	16 Drill Bit		

Datos técnicos

Largo(sin broca)	Peso(sin broca)	Diámetro externo	Vástago de broca	Rango de agujeros	Hilo de conexión
1413mm	303kg	Φ225mm	SD10	Φ254- Φ305mm	API 6 5/8 REG
Tamaño de caja	Tasa de impacto a 0.5 Mpa	Velocidad de rotación recomendada	Consumo de aire		
1620x275x290mm	20Hz	15-35 r/min	300-360(PSI)		
			950-1200(CFM)		