


HSD12 MARTILLO DE FONDO DTH

HSD12 Martillo	Descripción del Artículo	Peso Kg	Número de parte
	1 Top Sub	121.7	HSD12-01
	2 "O" Ring of Top Sub	0.02	HSD12-02
	3 Breakout Ring of Top Sub	2.10	HSD12-03
	4 Check Valve	2.10	HSD12-04
	5 Spring	0.20	HSD12-05
	6 Air Distributor	20.2	HSD12-06
	7 Internal Cylinder	31.3	HSD12-07
	8 Piston	110	HSD12-08
	9 External Cylinder	168.7	HSD12-09
	10 Retaining Ring	1.20	HSD12-10
	11 "O" Ring of Stop Ring	3.70	HSD12-11
	12 Stop Ring	0.03	HSD12-12
	13 Guided Sleeve	0.01	HSD12-13
	14 Breakout Ring of Stop Ring	1.20	HSD12-14
	15 Drive Chuck	0.35	HSD12-15
	16 Drill Bit	13.6	HSD12-16

Datos técnicos

Largo(sin broca)	Peso(sin broca)	Diámetro externo	Vástago de broca	Rango de agujeros	Hilo de conexión
1880mm	487Kg	Φ275mm	SD12	Φ305- Φ445	API 6 5/8 REG
Working Pressure	Tasa de impacto a 0.5 Mpa	Velocidad de rotación recomendada	Consumo de aire		
			1.0 MPa	1.8 MPa	2.4 MPa
1.0 - 2.5 MPa	16Hz	15-25 r/min	30 m ³ /min	56 m ³ /min	78 m ³ /min